Suite Wide

180

Elba Oak Platin

300

Luxor Oak Platin

320

Luxor Oak Gold

520

Luxor Oak Titanium

540

Elba Oak Brown

740

Kashmir Oak Silver

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Suite Wide

Experience 242mm extra-wide planks, highlighted by a charming V-groove and authentic wood texture. Our Suite Wide collection isn't just about style, it's for those who crave robust, low-maintenance floors. The Aqua Pearl tech shields against liquids, with 24-hour spill resistance. And with fantastic scratch resistance capabilities, life's chaotic, but your flooring doesn't have to be. Suite Wide: where style meets practicality.

Technical Data

Type:	Laminate Flooring
Dimensions:	1380mm x 242mm
Total Product Thickness:	8mm
Units Per Box:	8 boards
m² per box:	2.672
m² per pallet:	112.21
Colours:	6

Country of Origin:	Germany
Finish:	Matte
Surface:	Embossed in Register
Substrate Layer:	High Density Fibreboard
Backing Layer:	Balancing Layer
Profile:	4 Sided Bevel
Installation Method:	Uniclic®

Performance

Thermal Resistance:	(EN 12667) R=0,068m²K/W
Classification:	(EN ISO 10874) Residential 23, Commercial 32
Abrasion Rating:	(EN 13329) AC5
E3 Internal Moisture:	3.0 Watersplash - Alternative solution
Suitable for Wet Areas:	All wet areas - subject to proper installation and maintenance
Topical Moisture Resistance:	(ISO4760) No penetration through assembled join

Swelling after submersion in water:	(EN 24336) ≤12%
Impact Sound Reduction:	(ISO 10140-3) Ln,w 54dB / CI=0dB (EN ISO 717-2) ΔLw 19dB / CIΔ -9dB
Light Reflectance Values:	180 - 14.91 I 300 - 36.07 I 320 - 26.72 I 520 - 17.71 I 540 - 17.13 I 740 - 44.93
Flammability:	(EN ISO 9239) CRF 9.7kW/m2
Smoke Value:	(EN ISO 9239) 29% minutes
Slip Resistance:	(AS/NZ 4586-2013) P3, R10

Sustainability

Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	E1 lower than 0.05ppm

4 Sided Bevel

Embossed in Register

Easy To Clean

Uniclic®

Matte Finish

European Made

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Mid Range

Water Resistant Surface^

Wear Resistant

PEFC CoC Certified

All Godfrey Hirst Laminate floors must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Laminate Flooring Installation Instructions.
Warranty: All Godfrey Hirst floors carry a warranty supported by New Zealand after sales service. The Godfrey Hirst warranty is applicable to all Godfrey Hirst floors, sold in New Zealand. "As a New Zealand manufacturer, we endorse and recognise all rights of the consumer under the Consumer Guarantees Act 1993 (the "CGA") and further agree to match any performance guarantee or warranty offered in the market place, at the time of purchase, on any product which is equivalent to ours, where that performance guarantee or warranty offers rights to the consumer in addition to those under the CGA". For further information as to the warranty, installation, care and characteristic of this hard flooring please visit www.godfreyhirst.com or call 0800 500 210.
^Subject to proper installation, maintenance and local building code/regulatory approval.
~Test results and certificates are available on request.

godfreyhirst.co.nz